

Setback Distances in feet
 Becker County, Minnesota Table date: March 8, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
26	50	50	60	70
36	50	50	60	70
47	60	90	110	130
63	130	180	200	220
108	50	70	90	110
111	140	220	280	350
121	60	80	110	130
125	50	60	70	90
137	50	70	90	110
180	50	60	80	90
184	50	70	90	110
191	160	250	340	400
202	130	210	290	350
339	160	270	370	400
344	60	80	100	110
351	50	80	100	120
375	160	260	350	400
398	50	70	90	100
413	170	280	380	400
418	70	110	140	170
508	90	160	210	260
540	50	70	80	90
541	200	250	300	350
544	50	70	90	110
564	160	250	320	390
624	80	130	180	220
701	60	90	120	150
746	50	70	80	90
765	50	70	90	110
767	50	70	90	110
785	50	70	90	110
786	50	70	80	100
797	200	250	300	350
1111	50	110	200	290
1113	50	70	80	90

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
 Becker County, Minnesota Table date: March 8, 2012

1128	50	70	90	110
1129	50	80	100	120
1130	150	170	190	210
1135	50	60	70	90
1136	50	110	200	290
1138	160	250	330	400
1149	50	70	90	110
1200	60	90	110	140
1210	130	250	300	350
1211	60	90	110	140
1227	70	100	120	140
1230	50	70	80	90
1246	50	70	90	100
1251	80	140	200	260
1291	70	110	140	160
1306	130	220	300	370
1317	50	70	90	100
1318	50	70	90	100
1321	130	250	300	350
1365	120	190	250	320
1878	60	90	110	130
1938	50	60	70	80
1942	160	260	350	400
1967	50	70	90	110
1975	190	320	400	400
1997	50	70	90	100
1125B	120	200	270	340
1126B	160	280	380	400
1131B	160	280	380	400
1132B	110	180	240	290
1137B	50	50	70	80
1195B	110	200	270	330
1196B	100	190	260	330
1234B	50	50	60	70
1236B	110	180	240	290
1243B	60	80	110	130
1252B	110	190	250	310
1319B	160	270	360	400

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
 Becker County, Minnesota Table date: March 8, 2012

1320B	140	250	330	370
133A	50	70	90	110
133B	50	70	90	110
168B	50	70	90	100
171B	50	50	60	70
1825B	50	70	80	90
20B	60	90	110	130
267B	60	90	120	140
315A	120	200	260	320
315B	120	200	260	320
332B	120	200	260	320
33B	50	60	80	90
38B	50	70	90	100
406A	150	250	340	400
406B	150	250	340	400
40B	50	60	70	80
422B	50	70	90	110
567A	160	280	380	400
567B	160	280	380	400
711B	170	290	380	400
718B	50	70	100	110
747B	50	60	70	80
775B	120	210	290	350
778B	150	250	340	400
780B	50	60	70	80
867B	150	220	280	330
903B	50	60	80	90

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.