

Setback Distances in feet
Brown County, Minnesota Table date: March 8, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
35	80	120	140	160
85	60	90	120	140
86	50	60	70	90
113	50	60	70	90
114	50	60	80	90
130	50	60	80	100
136	60	90	110	130
140	60	90	110	140
227	130	220	290	370
247	140	220	290	320
269	50	50	50	60
281	90	150	200	250
282	130	230	320	380
313	50	60	80	100
317	60	80	110	130
336	50	50	60	80
386	50	70	90	110
423	50	70	80	100
463	70	100	130	160
487	80	150	230	280
495	80	150	210	270
499	110	200	270	380
518	110	170	220	270
574	50	60	70	90
575	50	60	70	90
603	70	100	120	150
639	110	190	250	310
919	50	60	70	90
929	90	150	200	250
946	100	180	250	320
968	120	200	270	330
1052	50	80	90	110
1833	50	50	70	80
1887	80	170	250	320
1909	120	210	290	360

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
Brown County, Minnesota Table date: March 8, 2012

1917	50	60	70	90
1928	160	280	390	400
1929	160	280	370	400
1930	140	220	290	360
102B	50	70	90	110
102B2	50	70	90	110
128B	70	110	140	170
27A	100	160	210	260
27B	100	160	210	260
327A	140	220	290	360
327B	140	220	290	360
41A	140	230	300	380
41B	140	230	300	380
421B	50	70	90	110
421B2	50	70	80	100
611B	140	230	300	370
820B	140	220	290	360
8B	140	220	280	340
920B	50	70	90	110
921B2	50	70	90	110
94B	50	70	90	100
954B2	50	70	90	100
999B	50	70	90	110
L13A	60	90	120	140
L163A	50	60	80	100
L201A	50	70	90	110
L83A	50	60	80	90
L84A	50	60	70	90
L85A	50	60	80	100

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.