

Setback Distances in feet
Chisago County, Minnesota Table date: March 8, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
75	50	70	80	100
161	130	220	290	360
162	100	180	250	310
182	80	170	240	300
265	80	160	220	290
265	80	160	220	290
274	130	220	300	380
292	50	70	100	120
325	50	50	50	50
337	130	230	330	390
346	50	70	90	110
540	50	70	80	90
543	50	110	210	290
544	50	70	80	90
545	50	70	80	90
565	130	210	240	270
677	50	50	50	60
726	130	170	200	220
792	120	210	290	360
1068	50	80	100	110
1977	70	90	100	100
1980	80	110	110	110
155B	170	270	360	400
158B	130	190	250	310
159B	90	140	170	210
169B	80	110	110	110
204B	60	90	120	140
207B	130	210	280	350
328B	150	230	300	360
40B	50	60	80	90
454B	150	240	310	380
676B	160	260	340	400
682B	80	110	120	120
717B	110	200	280	360
928B	130	200	260	320

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
Chisago County, Minnesota Table date: March 8, 2012

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.