

Setback Distances in feet  
 Clearwater County, Minnesota      Table date: February 3, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
63	130	180	200	220
111	140	220	280	350
121	60	80	110	130
125	50	60	70	90
180	50	60	80	90
202	130	210	290	350
205	130	210	280	350
272	150	190	220	250
346	60	80	100	120
426	150	210	230	250
432	110	200	220	240
435	100	150	190	230
439	140	190	210	230
481	130	240	260	280
540	50	70	80	90
543	50	110	200	290
544	50	70	90	110
547	170	270	360	400
561	50	70	120	140
563	90	130	150	180
564	160	250	320	390
565	130	210	240	270
582	50	70	90	110
607	70	110	130	160
627	50	100	190	280
650	60	80	90	110
672	70	100	130	160
702	50	70	120	140
712	150	260	360	400
713	130	190	210	230
733	50	100	150	170
737	60	80	100	120
746	50	70	80	90
765	50	70	90	110
767	50	70	90	110

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet  
 Clearwater County, Minnesota      Table date: February 3, 2012

797	200	250	300	350
799	50	70	80	90
1113	50	70	80	90
1164	130	200	240	260
1191	170	260	360	400
1200	60	90	110	140
1294	60	80	100	120
1325	50	70	80	90
1808	50	110	200	290
1874	160	270	360	400
1878	60	90	110	130
1943	130	210	270	330
1152B	140	230	310	380
1166B	120	200	260	320
1272B	60	80	110	130
133B	50	70	90	110
167A	60	90	120	140
169B	160	180	200	220
20B	60	90	110	130
242B	160	270	360	400
258B	150	250	340	400
267B	60	90	120	140
38B	50	70	90	100
40B	50	60	70	80
496B	130	200	270	330
505B	70	100	130	160
709B	150	180	210	240
718B	50	70	100	110
775B	120	210	290	350
867B	150	220	280	330
B109A	50	70	80	90
B200A	50	80	100	120
B201A	50	80	90	110
B202A	50	70	90	110
B203A	90	130	150	180
B204A	50	70	90	110
B206A	60	90	110	130
B207A	140	240	300	330

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet  
Clearwater County, Minnesota      Table date: February 3, 2012

B208A	150	210	240	270
B210A	130	210	240	270
B211A	50	100	150	170

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.