

Setback Distances in feet
 Cottonwood County, Minnesota Table date: March 8, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
1024A	50	50	60	70
L104A	50	60	80	90
L107A	50	70	80	100
L111A	50	70	90	100
L112A	50	70	80	100
L129B	50	70	90	110
L135A	60	90	110	130
L141A	50	50	70	80
L142A	50	50	60	80
L143A	160	280	380	400
L144A	60	80	100	120
L149A	50	60	80	90
L150A	60	80	100	120
L151A	50	70	80	100
L159A	50	70	90	110
L160B	70	150	180	190
L162B	50	70	80	100
L163A	50	60	80	100
L165A	150	280	390	400
L167A	110	200	270	340
L168A	120	220	300	370
L169A	120	200	270	330
L16A	50	70	80	90
L170B	130	210	280	350
L173A	50	50	70	80
L175A	50	60	80	90
L176A	60	140	200	250
L178A	130	260	370	400
L183A	170	300	400	400
L183A	170	300	400	400
L188A	50	70	80	100
L189A	120	260	370	400
L193A	50	130	190	240
L194A	70	190	280	360
L196A	60	90	110	130

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
 Cottonwood County, Minnesota Table date: March 8, 2012

L197A	150	280	390	400
L197A	150	280	390	400
L198A	50	50	60	70
L198B	50	50	60	70
L201A	50	70	90	110
L202A	50	50	70	80
L203A	50	60	80	100
L208B	50	70	80	100
L209A	50	60	70	80
L211B	50	70	90	110
L213A	60	90	110	130
L215A	130	220	300	370
L215B	130	220	300	370
L218B	50	70	90	110
L219A	50	50	60	70
L223B	50	70	90	110
L224A	50	50	60	70
L225B	50	50	70	80
L227B	60	90	110	130
L228B	50	70	80	100
L229A	50	60	80	90
L230A	90	200	230	240
L232A	50	50	100	160
L233A	60	90	110	140
L234A	50	60	80	90
L235A	80	190	280	350
L236A	50	100	140	180
L238A	50	60	80	90
L239A	50	60	80	90
L240A	50	100	170	220
L242B	50	70	80	100
L245A	50	100	140	180
L248B	50	50	70	80
L249A	50	70	80	100
L257A	70	150	240	320
L46B	90	190	260	330
L5A	50	60	70	90
L5A	50	60	80	100

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
 Cottonwood County, Minnesota Table date: March 8, 2012

L67B	60	80	110	120
L69B	80	120	150	180
L6A	100	180	250	310
L73A	70	100	130	150
L74A	130	210	280	350
L78A	50	70	80	100
L79B	50	70	80	100
L7A	100	180	250	310
L82A	50	60	80	100
L83A	50	60	80	90
L84A	50	60	70	90
L85A	50	60	80	100
L86A	60	80	110	130
L87A	60	90	120	140
L88A	50	80	100	120
L89A	50	60	80	90
L94A	80	110	140	160
L96B	130	210	280	350
L98A	50	60	80	100
L99B	50	70	80	100

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.