

Setback Distances in feet
 Dakota County, Minnesota Table date: March 8, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
1821	100	160	200	250
98	50	80	90	110
109	50	60	80	90
113	50	60	70	90
114	50	60	80	90
129	100	180	260	320
176	50	80	100	120
189	60	100	130	160
208	130	240	330	400
226	60	80	100	120
239	50	70	80	100
250	60	90	110	120
252	150	280	380	400
253	50	60	80	90
255	90	190	270	350
313	50	50	60	70
317	50	70	90	110
318	80	150	230	290
344	50	70	80	100
378	50	50	60	70
414	50	60	70	80
463	70	100	130	150
465	90	170	230	300
495	90	160	220	290
522	200	250	300	350
539	50	70	80	90
540	50	70	80	90
545	50	70	80	90
1055	50	70	80	90
1815	100	160	230	300
1816	60	90	110	130
1824	60	90	110	120
106B	50	60	80	90
12C	220	350	400	400
150B	60	100	130	160

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
 Dakota County, Minnesota Table date: March 8, 2012

155B	170	270	360	400
177A	100	150	190	230
177B	100	150	190	230
1825C	50	70	80	90
1894B	90	130	170	210
1895B	80	150	210	270
1896B	50	60	70	80
1902B	70	110	140	180
203B	60	100	120	150
213B	50	60	80	90
279B	60	110	140	170
27A	100	160	210	260
27B	100	160	210	260
283A	160	250	320	390
283B	160	250	320	390
285A	70	100	120	150
285B	70	100	120	150
2B	50	60	70	80
301B	80	110	140	170
320B	70	110	130	160
342B	70	100	130	160
377B	50	70	80	90
382B	60	80	110	130
39A	130	270	330	400
39B	130	270	370	400
39B2	130	270	370	400
409B	130	210	280	350
411A	140	260	380	400
411B	140	260	380	400
415A	170	280	380	400
415B	170	280	380	400
41A	140	230	300	380
41B	140	230	300	380
42C	200	330	400	400
449B	50	70	90	100
454B	150	230	300	370
49B	150	260	340	400
7A	110	220	310	370

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
Dakota County, Minnesota Table date: March 8, 2012

7B	130	250	350	400
888B	70	100	130	160
889B	170	310	400	400
895B	70	100	130	150
8A	140	220	280	340
8B	140	220	280	340
94C	50	70	80	100

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.