

Setback Distances in feet  
 Faribault County, Minnesota      Table date: March 6, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
101B	60	90	110	130
102B	50	80	100	120
1052	50	80	90	110
110	50	70	80	100
110	50	70	80	100
113	50	60	70	90
114	50	60	70	90
118	50	70	80	100
128B	80	110	140	170
130	50	80	90	110
134	50	60	80	100
136	60	80	110	130
140	70	100	130	150
160	90	140	190	240
181	80	160	230	290
1833	50	50	70	80
1834	50	50	70	80
1877	50	80	110	140
1907	70	100	130	150
197	70	100	130	150
211	50	70	90	110
229	50	70	90	110
230A	50	60	70	80
230B	50	60	70	80
247	125	210	280	310
248	60	90	120	140
255	110	200	270	340
269	50	50	60	70
275B	50	70	90	110
275C2	50	70	90	110
27B	90	150	200	250
27C	90	150	200	250
281	90	140	190	230
286A	50	70	90	100
286B	50	70	90	110

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet  
 Faribault County, Minnesota      Table date: March 6, 2012

286C2	50	70	90	110
287	50	70	90	110
310	50	80	100	130
313	50	60	80	100
319	50	70	90	110
336	50	70	80	100
35	70	100	130	160
37B	60	80	100	120
37B	60	80	100	120
392	120	240	340	400
41B	140	230	300	370
525	50	110	140	170
539	50	70	90	120
84	50	60	80	90
86	50	70	80	100
887B	50	70	90	110
8B	120	200	260	320
909C2	70	110	130	160
920B	50	70	90	110
920C2	50	70	90	110
921C2	50	70	90	110
929	90	140	190	240
94B	50	70	90	110
94B	50	70	90	110
956	50	60	70	90
96A	50	70	90	110
96A	50	70	90	110
96B	50	70	90	110
96B	50	70	90	110
L107A	50	70	90	100
L83A	50	60	80	90
L84A	50	60	70	90
L85A	50	60	80	100

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.