

Setback Distances in feet
Hubbard County, Minnesota Table date: March 8, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
147	60	90	120	140
170	130	150	170	190
202	130	210	290	350
260	130	220	290	307
261	120	210	270	340
346	60	80	100	120
488	50	70	90	110
540	50	70	80	90
541	200	250	300	350
545	50	70	90	110
628	60	80	100	120
672	70	100	130	160
701	60	90	120	150
746	50	70	80	90
797	200	250	300	350
799	50	70	80	90
1111	50	110	200	290
1113	50	70	80	90
1136	50	110	200	290
1164	130	200	240	260
1200	60	90	110	140
1230	50	70	80	90
1271	130	210	270	330
1294	60	80	100	120
1334	160	250	320	380
1336	140	250	330	370
1439	50	70	90	110
1444	160	250	330	400
1445	50	110	200	290
1447	50	60	70	90
1943	130	210	270	330
1956	170	280	310	340
1968	200	320	400	400
1969	200	300	400	400
1126B	160	280	380	400

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
Hubbard County, Minnesota Table date: March 8, 2012

1272B	60	80	110	130
1319B	160	270	360	400
1320B	140	250	330	370
1332B	160	270	360	400
133B	50	70	90	110
139B	160	250	320	380
1421B	160	270	360	400
1438B	160	180	200	220
1440B	150	240	320	390
1450B	170	280	370	400
1460B	50	60	70	80
158B	120	190	250	300
167A	60	90	120	140
207B	150	240	310	380
267B	60	90	120	140
406A	150	250	340	400
526C	80	120	140	170
567A	160	280	380	400
675C	160	270	370	400
709B	150	180	210	240
719B	50	70	90	110
731A	170	280	370	400
744B	70	100	130	160
775B	120	210	290	350
778B	150	250	340	400
820B	60	90	120	140
82B	150	240	320	390
82C	150	240	320	390
844B	170	280	370	400
867B	150	220	280	330

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.