

Setback Distances in feet  
 Itasca County, Minnesota      Table date: March 8, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
72	50	70	90	110
147	60	90	110	130
202	110	200	270	340
243	50	50	70	80
533	50	70	80	90
541	200	250	300	350
544	50	70	80	90
549	200	250	300	350
550	50	70	80	90
614	50	50	70	80
615	90	150	190	230
616	50	50	60	70
621	50	70	80	100
625	170	220	260	290
627	100	170	230	290
628	60	80	100	120
630	60	80	100	120
797	200	250	300	350
798	70	100	130	160
799	50	70	80	90
869	200	250	300	350
872	110	170	220	260
995	50	70	80	90
1031	50	70	80	90
1043C	60	90	110	140
158B	120	190	240	300
167B	60	90	120	150
240B	50	60	70	80
268B	170	280	370	400
32B	50	60	70	90
617B	110	200	270	340
618B	60	100	130	150
624B	50	80	100	120
626B	50	50	60	70
629B	90	140	180	220

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet  
Itasca County, Minnesota      Table date: March 8, 2012

801B	100	120	140	150
803B	50	50	60	80
866B	120	200	260	320
867B	140	220	280	340
868B	150	240	310	380
870C	70	100	130	150

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.