

Setback Distances in feet
 Kanabec County, Minnesota Table date: March 7, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
1013A	50	70	80	90
1017A	70	100	130	150
1020A	50	70	80	90
1023A	50	70	80	90
1025A	70	100	130	150
1026A	70	100	130	150
1026A	70	100	130	150
C101A	200	250	300	350
C102A	100	170	230	290
C103A	100	170	230	290
C105A	100	120	140	150
C106B	50	70	90	110
C107A	70	110	150	180
C108A	80	210	310	400
C109A	140	230	310	380
C10B	110	160	170	180
C110A	140	270	370	400
C112A	150	250	330	400
C112A	140	230	310	380
C112B	150	250	330	400
C112B	140	230	310	380
C113A	120	210	280	350
C116B	70	90	100	100
C117A	90	120	140	160
C119A	110	160	170	180
C11B	70	90	100	100
C123B	80	110	120	120
C124A	90	120	140	160
C125A	140	250	340	400
C126B	50	80	110	130
C127A	70	90	100	220
C12A	110	160	170	180
C130B	70	90	100	100
C133A	110	160	170	180
C134A	60	90	120	140

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
 Kanabec County, Minnesota Table date: March 7, 2012

C135A	110	240	340	400
C135B	110	240	340	400
C138B	50	70	80	100
C139A	80	210	320	400
C141C	150	280	380	400
C142A	90	160	230	280
C143B	70	110	130	160
C144A	100	240	340	400
C146A	60	70	80	80
C15B	110	160	170	180
C16A	140	240	320	390
C16B	140	240	320	390
C17A	130	260	360	400
C17B	130	260	360	400
C18B	50	70	100	120
C19A	50	70	80	100
C1B	80	110	120	120
C21A	50	70	90	100
C23B	150	280	380	400
C24A	160	290	400	400
C25A	50	80	100	120
C26A	60	80	100	110
C27A	130	250	360	400
C31B	50	70	80	100
C33B	80	130	160	200
C35A	140	280	380	400
C3B	70	90	100	100
C40A	150	270	370	400
C44A	140	250	330	400
C49A	150	280	380	400
C61A	50	60	80	90
C6A	90	120	140	160
C75A	50	70	80	90
C85A	50	70	90	110
C86A	60	70	80	90
C87A	90	160	230	280
C88A	90	160	220	270
C91B	80	110	120	120

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
Kanabec County, Minnesota Table date: March 7, 2012

C93A	200	250	300	350
C95A	50	70	80	90
C96A	60	90	100	100
C97A	100	170	230	290
C9A	70	90	100	100

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.