

Setback Distances in feet
Kandiyohi County, Minnesota Table date: March 8, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
35	80	120	160	190
39	160	270	370	400
84	50	60	70	90
94	50	70	80	100
110	50	60	70	80
112	50	50	60	70
113	50	60	80	90
114	50	60	70	90
134	50	70	90	100
140	60	90	110	140
336	50	50	70	90
392	130	230	320	400
399	100	170	220	300
413	170	280	370	400
423	50	70	80	100
444	50	60	80	90
447	50	80	100	120
523	50	70	80	100
525	50	70	140	170
539	50	70	100	120
548	50	150	240	380
559	50	60	80	100
566	170	290	380	400
613	90	130	170	210
817	50	60	80	90
899	50	50	60	80
927	50	50	60	70
981	50	60	80	90
1016	50	60	70	90
1055	50	50	70	80
1900	50	60	80	100
1908	140	240	330	400
1065B	50	50	60	70
106B	50	60	80	90
130A	50	60	80	100

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
Kandiyohi County, Minnesota Table date: March 8, 2012

130B	50	70	80	100
230A	50	60	70	80
230B	50	60	70	80
238B	60	80	100	120
27B	100	160	210	260
41A	140	230	300	380
446A	50	70	90	110
446B	50	70	90	110
804B	80	110	140	170
805B	90	140	180	220
806C	50	50	70	80
807B	70	110	140	170
819B	150	240	320	400
833B	90	140	180	220
875B	140	230	300	370
897B	50	70	80	100
954B	50	70	90	100
999B	50	70	90	100
L13A	60	90	120	140
L163A	50	60	80	100
L164A	50	70	80	100
L184A	50	50	50	60
L185B	50	50	50	50
L186A	50	50	60	60
L186A	50	50	50	60
L187A	60	90	100	120
L191A	80	120	140	160
L192A	50	70	80	90
L195A	70	110	130	150
L200A	50	80	90	100
L201A	50	70	90	110
L307B	90	140	180	220
L316B	70	130	180	230
L317A	60	110	160	200
L318A	60	110	150	190
L321A	60	100	140	180
L322A	70	120	160	200
L323A	80	130	170	210

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
Kandiyohi County, Minnesota Table date: March 8, 2012

L324A	80	110	150	170
L324A	80	120	150	180
L325A	70	110	150	180
L331A	60	120	170	220
L332A	80	120	160	190
L333A	80	120	160	190
L334A	50	70	140	170
L335A	50	70	110	160
L335A	50	70	110	160
L336A	50	100	140	180
L337B	90	140	180	220
L33A	50	50	50	60
L33B	50	50	50	60
L340B	90	140	180	220
L347A	50	90	130	160
L34A	50	50	50	60
L351A	50	70	140	170
L354A	90	140	190	230
L355B	80	120	150	180
L357B	80	120	150	180

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.