

Setback Distances in feet
 Koochiching County, Minnesota Table date: March 8, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
1020A	50	70	80	90
A15A	50	60	80	90
A16B	50	60	80	100
A17B	50	60	80	90
A18A	50	60	80	90
A19A	60	80	100	120
A20B	50	60	80	90
A22A	60	80	100	120
A25A	50	60	70	90
A30C	50	60	70	80
A31A	90	130	150	180
A32A	200	250	300	300
A33A	130	150	170	190
A34A	200	250	300	350
A35A	130	240	260	280
A36A	200	250	300	300
A37B	130	240	260	280
A38A	50	70	90	110
A39B	150	210	240	270
A40A	70	100	120	140
B146A	50	80	100	120
B151A	50	80	100	120
B18A	50	60	80	90
B19B	50	60	80	100
B1C	50	80	100	120
B23A	50	60	80	90
B243A	60	90	110	130
B247A	100	160	210	250
B248A	110	180	250	310
B249A	150	230	300	360
B24B	50	60	80	100
B250A	130	210	270	330
B251B	140	220	290	350
B255A	50	70	80	90
B256A	50	70	90	110

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
 Koochiching County, Minnesota Table date: March 8, 2012

B257A	200	250	300	300
B259A	200	250	300	300
B25B	50	60	80	90
B260A	200	250	300	350
B261A	200	250	300	350
B262A	70	100	120	140
B264B	80	210	300	390
B274A	200	250	300	350
B275A	200	250	300	350
B276A	50	70	90	110
B277A	200	250	300	350
B278A	200	250	300	350
B279A	50	110	200	290
B280A	70	100	130	160
B2A	50	70	90	100
B3B	50	70	90	110
B42B	50	80	100	120
B43A	90	130	150	180
B44B	150	210	240	270
B46A	70	100	120	140
B49B	50	80	100	120
B4A	50	70	90	100
B50A	50	80	100	120
B51A	130	150	170	190
B55A	50	80	100	120
B56A	60	90	120	140
B57B	60	100	140	170
B58B	160	250	330	400
B5B	50	70	90	110
B60B	130	240	260	280
B6B	150	170	190	210
B70A	130	240	260	280
B71A	100	160	210	250
B76A	110	170	230	280
B77A	130	210	290	350
B78B	150	220	280	330
B79B	120	220	300	370
B80A	200	250	300	350

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
 Koochiching County, Minnesota Table date: March 8, 2012

B82A	200	250	300	350
F168A	50	60	80	90
F169B	50	60	80	100
F189B	50	60	80	90
F190B	50	60	80	100
F191A	60	100	140	170
F193A	50	60	80	90
F196A	60	90	120	140
F197B	150	210	240	270
F199B	150	210	240	270
F200A	90	130	150	180
F201B	220	360	400	400
F202B	130	240	260	280
F2B	170	280	390	400
F41B	160	250	330	400

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.