

Setback Distances in feet
 LeSueur County, Minnesota Table date: March 8, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
35	80	120	160	190
86	50	60	70	90
109	50	60	70	80
114	50	60	80	90
123	50	50	60	70
129	100	200	280	350
183	70	100	130	150
256	50	70	80	100
271	70	100	130	160
317	60	90	110	140
323	50	70	80	100
329	50	60	70	90
392	120	240	340	400
414	50	60	70	80
463	70	100	130	160
468	70	100	120	150
525	50	70	140	170
539	50	70	90	120
978	50	60	70	80
1962	50	70	80	100
106B	50	60	80	90
138B	50	80	100	110
156A	60	180	300	400
156B	60	180	300	400
1901B	50	70	80	100
206B	120	250	350	400
238B	60	90	110	130
239B	50	70	90	110
27A	100	160	210	260
27B	100	160	210	260
327A	130	210	280	350
327B	130	210	280	350
39A	130	270	390	400
39B	130	270	390	400
41B	140	230	300	380

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
LeSueur County, Minnesota Table date: March 8, 2012

8B	140	220	280	350
944B	50	60	80	90
945B	50	60	80	90
94B	50	70	80	100

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.