

Setback Distances in feet  
 Lincoln County, Minnesota      Table date: March 8, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
J101B	50	60	80	100
J102A	50	60	80	90
J103A	50	60	80	90
J104A	50	60	80	90
J105A	170	290	400	400
J106B	50	70	80	100
J107A	50	60	80	90
J11A	50	60	70	90
J17A	50	70	90	100
J195B	50	60	80	90
J199A	50	60	80	90
J1A	50	50	70	80
J22A	140	220	290	360
J232B	50	70	80	100
J236A	50	60	80	90
J237A	50	50	60	80
J237B	50	50	60	80
J23A	50	80	100	120
J240B	50	50	60	70
J243A	50	50	60	70
J251A	50	50	60	70
J25A	50	80	110	130
J26B	50	70	90	100
J2A	50	80	100	120
J31B	170	290	400	400
J32A	50	70	80	100
J47A	50	60	80	90
J48A	50	60	80	100
J57A	50	60	80	100
J70A	50	150	260	360
J71A	50	60	70	80
J72B	140	220	290	360
J74A	150	270	370	400
J74B	150	270	370	400
J75A	140	250	340	400

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet  
 Lincoln County, Minnesota      Table date: March 8, 2012

J75B	140	250	340	400
J78A	50	60	70	80
J79B	50	50	60	80
J7B	100	180	240	300
J80A	50	80	100	120
J84A	70	120	170	210
J84B	70	120	170	210
J85A	90	180	250	320
J86B	50	50	60	80
J88B	50	60	70	80
J89B	50	70	80	90
J90B	50	60	70	80
J91B	70	110	130	140
J93A	50	70	80	100
J96B	50	60	80	100
J97B	50	60	80	90
J98A	50	50	70	80
J99A	50	60	70	90
L129B	50	70	90	110
L139A	170	310	400	400
L139B	170	310	400	400
L201A	50	70	90	110
L211B	50	70	90	110
L212A	60	80	100	120
L213A	60	90	110	130
L214A	60	80	110	130
L215B	130	220	300	370
L216A	50	60	70	90
L218B	50	70	90	110
L220A	60	80	110	130
L221A	50	60	70	90
L223B	50	70	90	110
L73A	70	100	130	150
L78A	50	70	90	100
L83A	50	60	80	90
L84A	50	60	70	90
L96B	130	210	280	350

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.