

Setback Distances in feet
 Martin County, Minnesota Table date: March 8, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
35	70	100	130	160
84	50	70	90	100
86	50	60	70	90
96	50	60	80	90
112	50	50	60	70
113	50	60	70	90
114	50	60	70	90
118	50	70	90	100
130	50	60	80	100
134	50	60	80	90
136	60	90	110	130
140	60	90	110	130
181	90	160	230	290
197	70	100	120	150
227	120	200	270	350
229	50	70	90	110
247	150	270	370	400
255	120	210	280	360
269	50	50	50	60
282	140	250	340	400
313	50	50	60	80
336	50	60	80	90
350	50	60	70	80
392	120	240	340	400
499	120	220	300	390
539	50	90	110	130
548	50	200	290	380
664	50	60	80	100
818	100	150	200	250
886	50	70	90	110
956	50	60	70	80
1052	50	80	90	110
1090	70	100	130	160
1833	50	50	70	80
1834	50	50	60	70

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
 Martin County, Minnesota Table date: March 8, 2012

1877	50	80	110	140
1907	70	100	130	160
101B	60	90	110	130
102B	50	80	90	110
106B	50	70	80	100
128B	80	110	140	170
275B	50	60	80	100
27B	90	160	220	270
37B	50	60	80	110
39B	150	290	390	400
41B	160	250	320	400
887B	50	80	90	110
8B	130	200	260	330
920B	50	80	90	110
921B	50	70	90	110
94B	50	60	80	90
L107A	50	70	90	100
L13A	60	90	120	140
L163A	50	60	80	100
L83A	50	60	80	90
L84A	50	60	70	90
L85A	50	60	80	100

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.