

Setback Distances in feet  
 Mower County, Minnesota      Table date: March 6, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
1030	60	80	110	130
1078	60	80	110	130
129	90	165	230	285
135	50	50	50	50
156A	170	310	400	400
156B	170	310	400	400
1812	70	140	200	260
1814B	50	70	90	100
1884	50	50	50	50
1891	50	70	90	110
190	140	250	340	400
1903	170	310	400	400
1904	170	310	400	400
1905	50	50	60	70
1974	50	60	70	90
1992	50	60	60	60
228B	90	130	170	210
228C	90	130	170	210
23	50	50	70	80
244A	110	170	220	280
244B	110	170	220	280
24B	50	50	50	60
252	140	260	360	400
253	50	60	70	90
255	110	200	270	340
27A	90	150	200	250
27B	90	150	200	250
295	50	60	80	90
2A	50	60	70	80
2B	50	60	70	80
307	50	60	70	80
30B	50	50	60	70
313	50	60	80	100
331	50	50	60	70
334B	50	50	70	80

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet  
 Mower County, Minnesota      Table date: March 6, 2012

	50	70	80	100
376B	50	70	80	100
377	50	60	80	90
380	50	60	70	90
381	50	60	70	90
382B	60	80	100	120
382C	50	60	80	90
393	170	300	390	400
44	60	90	110	130
444	50	70	80	90
465	110	210	300	370
467	50	80	100	120
479	50	60	70	80
483A	140	260	350	400
483B	140	260	350	400
485	120	220	300	380
516A	150	290	390	400
516B	150	290	390	400
517	70	170	250	330
539	50	70	90	120
631	50	60	70	80
632	50	70	90	110
633B	50	80	100	130
634	50	50	60	70
635	50	60	70	80
637	70	90	110	130
638B	50	70	90	110
638C	50	70	90	110
699A	50	90	110	140
699B	50	90	110	140
79B	90	170	260	320
83	50	60	80	90
88	50	70	90	110
99A	50	60	70	80
99B	50	60	70	80
99C	50	60	70	80

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.