

Setback Distances in feet
 Nobles County, Minnesota Table date: March 8, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
1015A	50	50	60	70
1024A	50	50	60	70
L107A	50	70	80	100
L111A	50	70	90	100
L112A	50	70	80	100
L126A	50	70	90	120
L127A	50	70	100	120
L129B	50	70	90	110
L130A	50	70	90	100
L133A	50	70	90	110
L134B	50	70	80	100
L135A	60	90	110	130
L136A	50	80	110	130
L137A	80	150	210	260
L138B	180	300	400	400
L139A	170	310	400	400
L139B	170	310	400	400
L140A	50	70	90	110
L141A	50	50	70	80
L144A	60	80	100	120
L145A	50	60	80	90
L146A	50	60	80	100
L150A	60	80	100	120
L151A	50	70	80	100
L155A	50	60	80	90
L159A	50	70	90	110
L160B	70	150	180	190
L162B	50	70	80	100
L163A	50	60	80	100
L170B	130	210	280	350
L5A	50	60	70	90
L5A	50	60	80	100
L6A	100	180	250	310
L78A	50	70	80	100
L79B	50	70	80	100

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
 Nobles County, Minnesota Table date: March 8, 2012

	50	60	80	90
L83A	50	60	80	90
L85A	50	60	80	100
L88A	50	80	100	120
L96B	130	210	280	350
L98A	50	60	80	100
P12B	50	60	80	90
P15B	60	90	110	130
P20B	70	100	120	140
P21A	50	70	80	90
P27A	50	70	90	110
P28A	50	60	80	90
P29A	50	60	80	90
P30B	50	60	80	90
P31A	60	90	110	130
P33A	60	90	110	140
P36A	100	190	260	330
P38B	130	220	290	360
P3A	110	200	270	340
P43A	50	60	70	80
P48A	90	170	230	290
P48B	90	170	230	290
P49A	50	70	90	110
P50B	50	60	70	80
P55A	110	190	260	330
P56A	190	340	400	400
P56B	190	340	400	400
P7A	50	70	90	110
P9A	50	70	80	100

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.