

Setback Distances in feet
 Olmsted County, Minnesota Table date: March 6, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
131B	60	90	90	90
131C	60	90	90	90
16	80	120	150	180
176	50	80	100	120
1811B	80	140	180	230
1812B	60	150	210	280
1832C	50	60	70	80
1846	120	230	310	400
19	60	90	120	140
203	60	90	120	140
209A	180	330	400	400
209B	100	180	240	300
216B	90	150	200	240
23	50	60	70	80
24	50	50	60	70
244C	110	170	220	280
25	100	170	230	290
252	140	260	360	400
27A	90	150	200	250
27B	90	150	200	250
27C	90	150	200	250
283B	150	240	310	380
283C	150	240	310	380
285A	70	110	130	160
285B	70	100	130	160
285C	70	100	130	160
289	50	80	100	120
295	50	60	70	80
298	60	170	260	360
2A	50	60	70	80
2B	50	50	70	80
301B	80	110	140	170
301C	80	110	140	170
309C	50	50	50	50
30B	50	50	50	60

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
 Olmsted County, Minnesota Table date: March 6, 2012

312B	50	50	50	50
312C	50	50	50	50
313	50	60	80	100
322C	70	100	140	160
333	60	90	120	150
369B	60	80	90	110
369C	60	80	90	110
378	50	50	60	70
401B	80	120	150	180
401C	80	120	150	180
401C2	80	120	150	180
463	90	150	200	250
465	110	210	300	370
467	50	80	100	120
468	80	110	130	160
471	80	120	150	180
474B	50	50	50	50
477A	60	90	120	140
477B	70	100	130	160
478B	50	50	60	70
479	50	60	70	80
483A	140	260	350	400
483B	140	260	350	400
485	120	220	300	380
486	140	260	360	400
487	90	170	230	290
493B	60	100	130	160
493C	60	100	130	160
495	100	200	270	340
516A	150	290	390	400
516B	150	290	390	400
516C	150	290	390	400
528B	50	90	110	130
99B	50	70	80	90
99C	50	70	80	90

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.