

Setback Distances in feet
Roseau County, Minnesota Table date: February 3, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
47	60	90	110	130
52	160	250	270	290
59	150	210	230	250
64	130	200	260	330
65	160	210	230	250
67	60	80	100	110
77	50	80	100	120
111	140	220	280	350
116	130	210	270	330
117	150	230	300	360
133	50	70	90	110
145	130	210	230	250
147	60	90	120	140
187	60	110	140	160
191	160	250	340	400
202	130	210	290	350
205	130	210	280	350
280	140	240	300	330
383	60	90	110	140
384	60	90	110	140
387	50	70	90	110
404	50	80	90	110
412	150	240	330	350
432	110	200	220	240
433	90	140	180	220
435	100	150	190	230
439	140	190	210	230
481	130	240	260	280
482	150	210	240	270
532	100	170	240	310
534	200	250	300	350
540	50	70	80	90
541	200	250	300	350
543	50	110	200	290
544	50	70	90	110

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
Roseau County, Minnesota Table date: February 3, 2012

546	50	70	80	90
547	170	270	360	400
550	70	100	120	140
561	50	70	120	140
563	90	130	150	180
565	130	210	240	270
570	140	240	330	400
581	60	90	110	140
582	50	70	90	110
583	50	70	90	110
627	50	100	190	280
630	60	80	100	120
643	150	210	230	260
644	50	80	100	120
645	150	210	230	260
651	140	210	230	250
708	160	270	360	400
712	150	260	360	400
733	50	100	150	170
737	60	80	100	120
755	50	60	80	90
767	50	70	90	110
794	150	260	360	400
1031	50	70	80	90
1144	140	190	210	230
1158	70	100	140	160
1170	70	100	140	160
1181	160	270	370	400
1182	130	150	170	190
1187	70	100	120	140
1191	170	260	360	400
1206	150	230	300	360
1214	50	70	90	110
1298	70	120	150	190
1302	150	210	230	250
1305	150	210	230	260
1314	70	100	120	140
1316	130	200	220	240

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
 Roseau County, Minnesota Table date: February 3, 2012

1326	160	250	270	290
1328	90	130	150	180
1333	70	100	120	140
1401	150	210	240	270
1402	140	230	310	380
1404	50	100	150	170
1405	50	80	110	130
1414	50	70	90	110
1428	200	340	400	400
1444	150	260	340	400
1448	50	70	90	110
1449	50	80	100	120
1807	50	70	90	110
1808	50	110	200	290
1918	140	160	180	200
1984	120	220	290	350
1133B	140	230	280	320
1179B	150	170	190	210
1274B	130	210	270	330
1327B	150	260	340	400
1399B	120	200	270	330
158B	120	190	250	300
167B	60	90	120	140
242B	160	270	360	400
48B	110	180	230	280

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.