

Setback Distances in feet
Steele County, Minnesota Table date: March 6, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
Ad	50	70	90	120
Af	50	70	100	120
Bc	120	240	340	400
Bd	120	240	340	400
BIA	170	300	400	400
BIB	170	300	400	400
BIB2	180	310	400	400
BIC2	180	310	400	400
BoB2	60	80	100	120
BoC2	60	80	100	120
BuB	140	240	330	400
BuC	140	240	330	400
Ca	60	90	110	130
Cc	50	60	80	90
Cd	50	60	70	90
Ce	50	60	70	80
Cf	50	60	70	80
ChD	110	170	220	270
CkB2	50	60	70	80
CIB	50	70	90	110
CIB2	50	70	90	110
CIC2	50	70	90	110
CsC2	50	70	90	110
Ct	50	80	90	110
Cu	50	80	90	110
DaA	130	250	350	400
DaB	130	250	350	400
DaC	130	250	350	400
DkA	130	250	350	400
DkB	130	250	350	400
DtA	90	150	200	250
DtB	90	150	200	250
Du	50	50	60	80
EaA	140	230	300	370
EaB	140	230	300	370

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
 Steele County, Minnesota Table date: March 6, 2012

EaC	140	230	300	370
Gc	50	60	70	90
Hk	150	260	350	400
Hm	50	60	70	90
HnB2	50	50	60	70
HnC2	50	50	60	70
HoB	50	50	60	70
HoB2	50	50	60	70
HoC	50	50	60	70
HoC2	50	50	60	70
Hs	120	260	360	400
Kc	120	230	310	400
Kd	120	230	310	400
Ke	120	230	310	400
Kf	120	230	310	400
KkB2	60	80	100	120
KkC2	60	80	100	120
LcB	90	140	190	230
LcC	90	140	190	230
Ld	130	220	290	370
LeB	50	80	100	120
LeB2	50	80	100	120
LIB	50	60	80	90
LIB2	50	60	80	90
LIC	50	60	80	90
LIC2	50	60	80	90
LmB2	50	60	80	90
LoC2	50	60	80	90
LuA	50	60	70	80
LuB	50	60	70	80
Ly	50	70	90	110
Ma	60	80	100	130
Mc	50	60	80	90
Mh	120	200	270	340
Mm	50	60	70	80
Mn	50	60	70	80
Mo	110	200	270	340
MrA	50	60	70	90

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
 Steele County, Minnesota Table date: March 6, 2012

MrB	50	60	70	90
MsA	50	70	80	100
MsB	50	70	80	100
MsB2	50	70	80	100
Mu	50	90	110	130
Mv	50	90	120	140
Mw	50	230	330	400
My	50	90	110	130
NbA	50	60	80	90
NcA	50	70	90	110
NcB	50	70	90	110
Sh	50	70	90	100
SkB	120	200	260	320
SkC	120	200	260	320
Ta	100	190	260	320
Ud	170	300	390	400
WaA	150	290	400	400
WaB	150	290	400	400
WaC2	150	290	400	400
WgA	130	250	370	400
WgB	130	250	370	400
Wt	50	60	80	90

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.