

Setback Distances in feet  
Stevens County, Minnesota      Table date: March 7, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
AaA	50	50	50	60
Af	70	130	170	220
Ar	80	120	160	200
BaA	50	60	70	90
BaB	50	60	70	90
BbB2	50	60	70	90
BdA	60	80	100	110
Be	80	140	200	250
Bf	80	140	200	250
Bh	90	130	150	180
Bm	90	140	190	230
Co	50	80	100	110
Cp	60	90	110	140
Cu	50	80	100	110
DaB	50	60	80	90
DIA	50	60	80	90
DIB	50	60	80	90
Do	50	80	100	120
Dv	50	80	100	120
EcB	70	100	130	150
EsA	150	270	380	400
FdA	110	220	300	380
FmA	50	70	90	100
FmB	50	70	90	100
FmB2	50	70	90	100
FuB2	50	70	90	100
GdA	90	150	200	240
GlA	80	120	160	200
GmA	80	120	160	200
HaA	50	70	80	100
HnB	50	70	90	100
Ho	50	60	80	100
Hw	50	60	80	90
Lm	70	130	180	220
Ln	70	130	180	220

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet  
Stevens County, Minnesota      Table date: March 7, 2012

Lp	50	80	100	120
MaB	150	230	300	370
Mc	140	230	320	400
MfA	110	200	270	340
Mh	200	250	300	350
Mr	110	200	280	350
MsA	50	70	90	110
Mu	70	120	150	190
Mv	70	120	150	190
Mw	70	90	120	140
NcA	50	60	80	90
NhA	50	60	80	90
Om	50	70	90	100
Pa	60	90	110	130
Pf	60	90	110	130
Ra	60	220	340	400
ReA	190	320	380	400
ReB	190	320	380	400
RoA	80	130	160	200
RzB	80	130	160	200
SgC	150	230	310	370
SsA	150	230	310	370
SsB	150	230	310	370
SvA	60	80	110	130
SwA	130	210	280	340
SwB	120	190	260	330
TaA	50	70	90	110
To	50	70	90	100
Va	50	50	60	70
Wn	50	60	80	90

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.