

Setback Distances in feet
 Todd County, Minnesota Table date: March 8, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
36	50	50	60	70
75	50	90	120	150
111	140	220	280	350
121	60	80	110	130
142	140	240	330	370
170	130	150	170	190
180	50	60	80	90
183	100	160	210	260
202	130	210	290	350
260	130	220	290	370
261	120	210	270	340
292	50	80	100	120
325	130	200	280	350
413	170	280	380	400
446	50	70	90	110
514	200	250	270	290
540	50	70	80	90
541	200	250	300	350
543	50	110	200	290
544	50	70	90	110
545	50	70	90	110
565	130	210	240	270
571	140	220	240	260
572	150	210	230	250
582	50	70	90	110
701	60	90	120	150
703	130	250	300	350
808	50	70	90	100
823	140	220	280	350
825	50	60	80	90
873	60	60	60	60
1926	50	70	80	90
1927	50	80	100	130
1932	60	90	120	150
1943	130	210	270	330

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
 Todd County, Minnesota Table date: March 8, 2012

1956	170	280	310	340
127A	120	200	270	340
127B	120	200	270	340
139B	160	250	320	380
144B	60	90	110	130
158B	120	190	250	300
163B	60	90	110	130
169B	160	180	200	220
200B	60	80	110	130
204B	50	80	110	130
207B	150	240	310	380
341A	170	290	380	400
341B	170	290	380	400
374B	160	270	360	400
38B	50	70	90	100
402C	190	290	380	400
406B	150	250	340	400
421B	50	70	80	100
453B	150	180	210	240
454B	170	260	330	400
458B	140	210	280	340
53B	70	110	140	170
720B	140	250	330	370
7A	120	220	310	370
7B	120	220	310	370
928B	60	80	110	130

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.