

Setback Distances in feet
 Winona County, Minnesota Table date: March 6, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
103A	70	100	130	160
103B	60	100	130	160
103C	60	100	130	160
176	60	80	110	130
1822B	120	170	210	250
1830	60	90	110	130
1857	60	90	110	130
1860	60	80	100	130
1861	50	70	90	110
1893B	70	120	160	200
19	60	90	110	140
194	80	110	140	170
1952B	60	100	100	100
1952C	60	100	100	100
1960B	50	50	50	50
198C	90	130	180	220
1990	70	100	120	150
215B	70	100	130	160
215C	70	100	130	160
24	50	50	60	70
25	100	170	230	290
262B	50	50	70	80
271	100	170	230	280
283B	150	240	310	380
283C	150	240	310	380
285A	70	110	140	170
285B	70	110	140	170
285C	70	110	140	170
301A	80	120	150	180
301C	80	120	150	180
322C2	70	100	140	160
331	50	50	60	60
369B	50	70	80	100
369C	50	70	80	100
388C	60	100	130	160

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
 Winona County, Minnesota Table date: March 6, 2012

401B	70	110	140	170
401C	70	110	140	170
455A	60	90	110	140
455B	60	90	110	130
468	80	110	140	170
474B	50	50	50	50
477	70	110	140	160
483	140	260	350	400
493B	70	110	130	160
522	200	250	300	350
576	70	110	140	170
577	70	110	140	170
578	70	110	130	160
580B	60	90	110	130
580C	60	90	110	130
586C	60	90	120	150
598B	60	90	110	130
604	80	110	140	170
606	50	70	80	100
79B	90	170	260	320
99B	50	50	60	70
99C	50	50	60	70

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.