

Setback Distances in feet  
 Wright County, Minnesota      Table date: March 8, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
35	70	100	120	140
86	50	70	80	100
106	50	60	80	90
109	50	70	80	100
114	50	60	70	90
138	50	70	80	100
181	110	160	210	260
229	50	70	90	100
231	50	60	80	90
235	50	70	90	100
239	50	60	80	90
247	140	220	290	320
255	120	210	300	400
256	50	70	90	100
260	140	240	320	400
261	110	210	290	360
323	50	60	80	90
375	140	240	330	400
392	130	250	350	400
406	130	250	350	400
414	50	60	80	90
441	120	270	390	400
511	70	120	160	190
523	50	70	80	90
525	50	70	140	170
539	50	70	80	90
540	50	70	80	90
543	50	110	210	290
548	50	150	240	380
603	60	100	140	180
708	140	230	300	360
740	50	60	80	100
768	170	310	400	400
771	110	240	340	400
792	120	210	290	360

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet  
 Wright County, Minnesota      Table date: March 8, 2012

799	50	70	80	90
956	50	70	80	100
978	50	70	80	100
1000	160	290	390	400
1075	50	70	80	90
1075	50	70	80	90
1080	50	70	80	90
1099	90	140	180	220
1110	110	210	290	350
1156	50	70	90	110
1163	80	130	170	210
1165	70	110	150	190
1173	50	70	140	170
1186	70	120	150	190
1197	60	100	130	150
1199	50	70	80	90
1203	50	70	80	90
1213	50	60	80	90
1220	50	60	80	90
1223	140	230	320	390
1224	140	260	360	400
1231	130	250	350	400
1255	130	260	360	400
1256	110	190	250	310
1257	110	240	340	400
1288	50	70	80	90
1368	60	150	280	390
1378	100	230	320	400
1381	50	80	100	110
1406	130	250	340	400
1942	150	250	330	400
1946	140	250	340	400
1975	170	290	400	400
1026B	80	130	170	210
1035B	100	160	250	330
1036B	50	60	80	90
1038A	180	320	400	400
1038B	180	320	400	400

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet  
 Wright County, Minnesota      Table date: March 8, 2012

1066B	140	260	370	400
1087B	50	60	80	90
1094B	50	60	80	90
1196B	130	230	310	380
1204B	50	70	90	100
1207B	50	70	90	100
1260B	170	300	400	400
1362B	50	60	80	90
1377B	130	250	350	400
1379B	220	400	400	400
1380A	60	100	120	150
1380B	60	100	120	150
1383A	50	70	90	100
1388B	50	70	90	110
1408B	50	60	80	90
158A	130	190	250	310
158B	130	190	250	310
1901B	50	60	80	90
258B	140	240	320	390
286B	50	60	80	100
294A	120	240	340	400
327A	120	200	270	340
327B	120	200	270	340
461B	60	80	110	130
74B	90	150	210	260
7A	130	250	350	400
7B	130	250	350	400
804B	80	120	150	180
875B	130	210	280	350
896B	70	100	130	160
8B	130	200	260	320
L307B	90	140	180	220
L317A	60	110	160	200
L318A	60	110	150	190
L320A	50	70	80	90
L324A	80	120	150	180
L330A	50	70	80	90
L331A	50	70	80	90

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet  
Wright County, Minnesota      Table date: March 8, 2012

L334A	50	70	140	170
L335A	50	70	110	160
L347A	50	90	130	160
L350A	60	110	150	180
L351A	50	70	140	170
L355B	80	120	150	180

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.