

Setback Distances in feet  
 Yellow Medicine County, Minnesota      Table date: March 8, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
35	70	100	120	140
85	60	80	100	120
86	50	60	70	90
108	50	70	90	110
113	50	60	80	90
134	50	60	80	100
137	50	70	80	100
140	60	90	110	130
160	70	120	160	200
210	50	70	80	100
246	150	260	360	400
276	50	70	90	100
319	50	80	100	130
347	150	260	350	400
371	100	160	220	270
423	50	60	80	100
434	50	70	90	110
444	50	60	80	90
574	50	70	90	110
575	50	60	70	90
597	50	80	100	120
610	60	80	100	120
878	60	80	100	120
883	100	200	280	360
1867	100	200	280	360
1868	50	60	70	90
1869	50	70	100	130
1870	60	80	100	120
127A	130	210	280	350
127B	120	210	280	340
141A	110	170	230	290
141B	110	170	230	290
290B	100	150	200	260
290B2	100	150	220	270
339A	150	260	360	400

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet  
 Yellow Medicine County, Minnesota      Table date: March 8, 2012

339B	150	260	360	400
341A	180	290	380	400
341B	180	290	380	400
402D	190	300	390	400
421B	50	70	80	100
591B	50	70	80	90
591B2	50	60	80	90
94B	50	60	80	90
954B2	50	70	90	100
954C2	50	60	80	100
969B2	90	140	170	210
J101B	50	60	80	100
J105A	170	290	400	400
J106B	50	70	80	100
J107A	50	60	80	90
J11A	50	60	70	90
J12A	160	300	400	400
J195B	50	60	80	90
J199A	50	60	80	90
J1A	50	50	70	80
J232B	50	70	80	100
J236A	50	60	80	90
J237A	50	50	60	80
J237B	50	50	60	80
J23A	50	80	100	120
J240B	50	50	60	70
J243A	50	50	60	70
J251A	50	50	60	70
J26B	50	70	90	100
J2A	50	80	100	120
J31B	170	290	400	400
J32A	50	70	80	100
J38B	80	120	160	190
J48A	50	60	80	100
J57A	50	60	80	100
J75A	140	250	340	400
J75B	140	250	340	400
J77A	50	80	100	120

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet  
Yellow Medicine County, Minnesota      Table date: March 8, 2012

J7A	100	180	240	300
J7B	100	180	240	300
J80A	50	80	100	120
L201A	50	70	90	110
L84A	50	60	70	90

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.